

COMPETITIVE COMPARISON GUIDE



- Superior Weatherproof Protection
- Interior & Exterior Projects
- Exceeds ASTM C920 Class 50 & TT-S-00230C
- Permanently Flexible – Will Not Crack



Titebond
THE PRO'S ADVANTAGE



	TITEBOND TITESHIELD™	DAP® DYNAFLEX 230[†]	Red Devil® Lifetime® Ultra 230[†]
INTERIOR/EXTERIOR USE ▶	Yes	Yes	Yes
PAINTABLE ▶	Yes, in 2-4 hours	Yes, in 2 hours	Yes, in 4-6 hours
SPECIFICATIONS ▶	AAMA 808.3-16 Type I ASTM C834 Type OP Grade -18 C ASTM C920 Type S Grade NS Class 50 (Clear is Class 25) Federal Specification TT-S-00230C Type II Class A	ASTM C920 Class 25	ASTM C920 Class 25 & TT-S-00230C Type II Class A
JOINT MOVEMENT CAPABILITY ▶	±50%	±25%	±25%
APPLICATION TEMPERATURE ▶	40°F to 120°F	40°F to 100°F	40°F to 90°F
GAP FILLING ▶	Up to 2" Wide	Up to 2" Wide	Up to 1" Wide
COLORS ▶	8 Colors & Clear	8 Colors & Clear	6 Colors & Clear
WEATHER RESISTANCE* ▶	No major changes	Extreme bubbling and chalking	Not tested
FREEZE/THAW STABLE ▶	Yes	Yes	Yes
VOC COMPLIANT ▶	Yes	Yes	Yes
SHELF LIFE ▶	2 Years	1 Year	1 Year

COMPETITIVE COMPARISON GUIDE

*Sealants were placed in a weathering device exposed to cycles of UV and moisture for 2000 hours.

[†]DAP and DYNAFLEX 230 are registered trademarks of DAP Global Inc. Red Devil and Lifetime are registered trademarks of Red Devil, Inc.

Visit Titebond.com for the most up-to-date product information.

Franklin International

Columbus, Ohio 43207 614.443.0241 Technical Service 1.800.347.4583 © 2023 01682_7428LN FF1380



Titebond
THE PRO'S ADVANTAGE